

MAIN PRODUCT

# SLIM CEILING LIGHT



**Feature:**By adjusting the switch behind the ceiling light, you can choose your preferred color temperature before installation, including 3000K(WL), 4000K(NW) and 6000K(DL).

<b>Material</b>	ABS+PS
<b>CRI</b>	>80
<b>Housing Color</b>	White/Black/Wood/Gold/Silvery
<b>IP Grade</b>	IP40
<b>Certification</b>	TUV CB CE EMC Erp



Model	Power	Size	CCT	Lumen	Voltage
FY101-D23023X-18W	18W	D230*23MM	3CCT	100lm/W	AC85-265V 60Hz
FY101-D30023X-24W	24W	D300*23MM	3CCT	100lm/W	AC85-265V 60Hz
FY101-D40025X-32W	32W	D400*25MM	3CCT	100lm/W	AC85-265V 60Hz
FY101-D50025X-40W	40W	D500*25MM	3CCT	100lm/W	AC85-265V 60Hz
FY101-D60027X-50W	60W	D600*27MM	3CCT	100lm/W	AC85-265V 60Hz
FY101-D75025X-70W	70W	D750*27MM	3CCT	100lm/W	AC85-265V 60Hz

# SLIM CEILING LIGHT



**Feature:**By adjusting the switch behind the ceiling light, you can choose your preferred color temperature before installation, including 3000K(WL), 4000K(NW) and 6000K(DL).

<b>Material</b>	ABS+PS
<b>CRI</b>	>80
<b>Housing Color</b>	White/Black/Wood/Gold/Silvery
<b>IP Grade</b>	IP40
<b>Certification</b>	TUV CB CE EMC Erp SAA

Model	Power	Size	CCT	Lumen	Voltage
FY101-D23023X-18W	18W	D230*23MM	3CCT	100lm/W	AC85-265V 60Hz
FY101-D30023X-24W	24W	D300*23MM	3CCT	100lm/W	AC85-265V 60Hz
FY101-D40025X-32W	32W	D400*25MM	3CCT	100lm/W	AC85-265V 60Hz
FY101-D50025X-40W	40W	D500*25MM	3CCT	100lm/W	AC85-265V 60Hz
FY101-D60027X-50W	60W	D600*27MM	3CCT	100lm/W	AC85-265V 60Hz
FY101-D75025X-70W	70W	D750*27MM	3CCT	100lm/W	AC85-265V 60Hz

# FRAMELESS PANEL LIGHT



**Feature:** Easy to install, the size of the back opening can be freely adjusted, and the iron material bottom plate has excellent heat dissipation performance and a more competitive price advantage

<b>Material</b>	Iron+PS
<b>CRI</b>	>80
<b>Housing shape</b>	Round/Square
<b>IP Grade</b>	IP20
<b>Certification</b>	CE EMC



Power	Size	Cut Size	CCT	Lumen	Voltage
Round 10W	Φ100mm	Φ50-75mm	3CCT	100lm/W	AC85-265V 60Hz
Round 15W	Φ120mm	Φ50-95mm	3CCT	100lm/W	AC85-265V 60Hz
Round 24W	Φ170mm	Φ50-140mm	3CCT	100lm/W	AC85-265V 60Hz
Round 36W	Φ225*mm	Φ50-190mm	3CCT	100lm/W	AC85-265V 60Hz
Square 10W	100*100mm	Φ50-75mm	3CCT	100lm/W	AC85-265V 60Hz
Square 15W	120*120mm	Φ50-95mm	3CCT	100lm/W	AC85-265V 60Hz
Square 24W	170*170mm	Φ50-140mm	3CCT	100lm/W	AC85-265V 60Hz
Square 36W	225*225mm	Φ50-190mm	3CCT	100lm/W	AC85-265V 60Hz

# DOB ABS PANEL LIGHT



**Feature:** Adopting a DOB driver free solution, it has a better price competitive advantage, with a light efficiency of up to 80lm/W, which can meet various types of usage environments,

<b>Material</b>	ABS
<b>CRI</b>	>80
<b>Housing shape</b>	Round/Square
<b>CCT</b>	3000K/4000K/6000K
<b>Certification</b>	CE EMC



Model	Power	Size	Cut Size	Lumen	Voltage
DOB-R100-5W	5W	Φ100*H24mm	Φ75mm	80lm/W	AC85-265V 60Hz
DOB-R120-7W	7W	Φ120*H24mm	Φ95mm	80lm/W	AC85-265V 60Hz
DOB-R145-12W	12W	Φ145*H24mm	Φ125mm	80lm/W	AC85-265V 60Hz
DOB-R170-16W	16W	Φ170*H24mm	Φ145mm	80lm/W	AC85-265V 60Hz
DOB-R220-22W	22W	Φ220*H24mm	Φ195mm	80lm/W	AC85-265V 60Hz
DOB-S120-7W	7W	120*120*24mm	95*95mm	80lm/W	AC85-265V 60Hz
DOB-S145-12W	12W	145*145*24mm	125*125mm	80lm/W	AC85-265V 60Hz
DOB-S170-16W	16W	170*170*24mm	145*145mm	80lm/W	AC85-265V 60Hz
DOB-S220-22W	22W	220*220*24mm	195*195mm	80lm/W	AC85-265V 60Hz

# DOB ABS PANEL LIGHT



**Feature:** Adopting a DOB driver free solution, it has a better price competitive advantage, with a light efficiency of up to 80lm/W, which can meet various types of usage environments,

<b>Material</b>	ABS
<b>CRI</b>	>80
<b>Housing shape</b>	Round/Square
<b>CCT</b>	3000K/4000K/6000K
<b>Certification</b>	CE EMC



Model	Power	Size	Driver	Lumen	Voltage
DOB-R170-16W	16W	Φ170*H24mm	DOB	80lm/W	AC85-265V 60Hz
DOB-R220-22W	22W	Φ220*H24mm	DOB	80lm/W	AC85-265V 60Hz
DOB-R280-32W	32W	Φ280*H24mm	DOB	80lm/W	AC85-265V 60Hz
DOB-S170-16W	16W	170*170*24mm	DOB	80lm/W	AC85-265V 60Hz
DOB-R220-22W	22W	220*220*H24mm	DOB	80lm/W	AC85-265V 60Hz
DOB-R280-32W	32W	280*280*H24mm	DOB	80lm/W	AC85-265V 60Hz

# ABS SPOT LIGHT



**Feature:** Adjustable luminous angle, PC lens anti glare design, with holes on the back of the lamp body for better heat dissipation and extended lamp life , very high Lumen about 100lm/W

<b>Material</b>	ABS
<b>CRI</b>	>80
<b>Housing shape</b>	Round/Square
<b>CCT</b>	3000K/4000K/6000K
<b>Certification</b>	CE EMC



Model	Power	Size	Cut Size	Lumen	Voltage
SP-R-3W	3W	Φ75*36mm	Φ55mm	90-100lm/W	AC85-265V 60Hz
SP-R-5W	5W	Φ91*36mm	Φ75mm	90-100lm/W	AC85-265V 60Hz
SP-R-7W	7W	Φ91*36mm	Φ75mm	90-100lm/W	AC85-265V 60Hz
SP-R-9W	9W	Φ112*38mm	Φ90mm	90-100lm/W	AC85-265V 60Hz
SP-R-12W	12W	Φ133*38mm	Φ115mm	90-100lm/W	AC85-265V 60Hz
SP-S-3W	3W	75*75*36mm	55*55mm	90-100lm/W	AC85-265V 60Hz
SP-S-5W	5W	91*91*36mm	75*75mm	90-100lm/W	AC85-265V 60Hz
SP-S-7W	7W	91*91*36mm	75*75mm	90-100lm/W	AC85-265V 60Hz
SP-S-9W	9W	112*112*38mm	90*90mm	90-100lm/W	AC85-265V 60Hz
SP-S-12W	12W	133*133*38mm	115*115mm	90-100lm/W	AC85-265V 60Hz

# FRAMELESS PANEL LIGHT



**Feature:** Super Bright & Energy Saving-200W UFO LED high bay light fixture at 6000K day light white provides 26000 Lumen output, equivalent to 600W HPS. Energy saving and user friendly.

<b>Material</b>	Aluminum+PC
<b>CRI</b>	>80
<b>Housing Color</b>	Black
<b>IP Grade</b>	IP65
<b>Certification</b>	ISO 9001 CE EMC



Model	Power	Size	CCT	Lumen	Voltage
UFO02100	100W	D250*15MM	3000K/4000K/6000K	110lm/W	AC85-265V 60Hz
UFO02150	150W	D300*15MM	3000K/4000K/6000K	110lm/W	AC85-265V 60Hz
UFO02200	200W	D350*15MM	3000K/4000K/6000K	110lm/W	AC85-265V 60Hz
UFO02240	240W	D350*15MM	3000K/4000K/6000K	110lm/W	AC85-265V 60Hz